

Drill Collars

| OD | ID | Connection | Bevel Diameter | Length | Make-up Torque | Torsional Strength | BSR | Weight (Slick) | Weight (Spiral) | Elevator Recess | Radius | OD | Slip Recess | Angle | |
|-------|---------|------------|----------------|--------|----------------|--------------------|------|----------------|-----------------|-----------------|--------|------|-------------|-------|-----|
| (in) | (in) | (in) | (in) | (ft) | (ft.lbs) | (ft.lbs) | | (lbs) | (lbs) | Depth | (in) | (in) | Depth | (in) | (°) |
| 4 3/4 | 2 1/4 | NC38 | 4 37/64 | 31 | 9,990 | 17,600 | 1.92 | 1,430 | 1,360 | 4 1/4 | 1/4 | 1/8 | 4 3/8 | 3/16 | 3.5 |
| 6 1/4 | 2 13/16 | NC46 | 5 29/32 | 31 | 22,400 | 39,500 | 2.64 | 2,550 | 2,420 | 5 5/8 | 5/16 | 1/8 | 5 3/4 | 1/4 | 5 |
| 6 1/4 | 2 13/16 | NC50 | 5 59/64 | 31 | 23,000 | 40,500 | 1.71 | 2,550 | 2,420 | 5 5/8 | 5/16 | 1/8 | 5 3/4 | 1/4 | 5 |
| 6 1/2 | 2 13/16 | NC46 | 6 3/32 | 31 | 22,400 | 39,500 | 3.07 | 2,810 | 2,660 | 5 7/8 | 5/16 | 1/8 | 6 | 1/4 | 5 |
| 6 1/2 | 2 13/16 | NC50 | 6 7/64 | 31 | 29,700 | 52,200 | 2.03 | 2,810 | 2,660 | 5 7/8 | 5/16 | 1/8 | 6 | 1/4 | 5 |
| 6 3/4 | 2 13/16 | NC46 | | 31 | 23,220 | | | 3,080 | 2,920 | 6 | 3/8 | 3/16 | 6 1/4 | 1/4 | 5 |
| 6 3/4 | 2 13/16 | NC50 | 6 19/64 | 31 | 32,300 | 56,800 | 2.37 | 3,080 | 2,920 | 6 | 3/8 | 3/16 | 6 1/4 | 1/4 | 5 |
| 8 | 2 13/16 | 6 5/8 Reg | 7 33/64 | 31 | 53,300 | 85,400 | 2.60 | 4,580 | 4,330 | 7 1/4 | 3/8 | 3/16 | 7 1/2 | 1/4 | 5 |
| 8 1/4 | 2 13/16 | 6 5/8 Reg | 7 45/64 | 31 | 53,300 | 85,400 | 2.93 | 4,910 | 4,630 | 7 1/2 | 3/8 | 3/16 | 7 3/4 | 1/4 | 5 |

SUPERIOR
DRILLPIPE
MANUFACTURING INC.

281-452-2260

7203 Miller Road #2 • Houston, Texas 77049 • sales@superiordrillpipe.com

superiordrillpipe.com



API 5DP-003
API 7-1-0849